



VT-SMKC1
VT-SMKC1/H
Side View Color Smoke Detector
Cameras



- Color CCD Image Sensor with 420 TV Lines (VT-SMKC1) / 550 TV Lines (VT-SMKC1/H)
- Minimum Illumination of 0.5 Lux
- Camera Mounted On Adjustable Gimbal To Achieve the Perfect Viewing Angle
- 3.6mm Standard lens Included (Optional 2.8mm to 25mm Available)
- Dimensions: 5.12" (OD) X 2.29" (H)

VITEK



CAUTION
RISK OF ELECTRICAL SHOCK
DO NOT OPEN




1. Unit contains uninsulated dangerous voltage within the enclosure that may be of sufficient magnitude to constitute a risk of electric shock to persons
2. Only use DC Power Supply
3. Read & Keep these instructions.
4. Heed to all warnings and follow all instructions carefully.
5. Do not use near water.
6. Clean only with dry cloth.
7. Do not block any ventilation openings. install in accordance with the instructions.
8. Do not install near any heat source such as radiators, heat resistors, stoves, or other apparatus (including amplifiers) that produce heat.
9. Do not defeat the safety purpose of the polarized or grounding-type plug. A polarized plug has two blades with one wider than the other. A grounding type plug has two blades and a third grounding prong. The wide blade or the third prong are provided for safety. If the provided plug does not fit into your outlet, consult an electrician for replacement of the obsolete outlet.
10. Protect the power cord from being walked on or pinched particularly at plugs, convenience receptacles, and the point where they exit from the apparatus.
11. Only use attachment/accessories specified by VITEK.
12. Use only with cart, stand, tripod, bracket, or table specified by the manufacturer, or sold with the Unit,
13. Unplug this unit during lightning storms or when unused for long periods of time.
14. Refer all servicing to qualified service personnel. Servicing is required when the unit has been damaged in any way, such as power-supply cord or plug is damaged, liquid has been spilled or objects have fallen into the unit, the unit has been exposed to rain or moisture, does not operate normally or has been dropped.
15. Do not attempt to service this product yourself as opening or removing covers may expose you to dangerous voltage or other hazards. Refer all servicing to qualified service personnel.

CAUTION - To reduce the risk of electric shock, do not perform any servicing other than contained in these operating instructions unless you are qualified to do so.

SPECIFICATIONS

SPECIFICATIONS	VT-SMKC1	VT-SMKC1/H
Image Device	1/4" DSP Color	1/3" DSP Color
Effective Pixels	510 x 492	768 x 492
Resolution	420 TV Lines	550 TV Lines
Minimum Illumination	0.5 Lux	
S/N Ratio	More Than 48dB	
Electronic Shutter	1/60 to 1/100,000 sec.	
AGC	On	
Sync. Mode	Internal Sync.	
Scanning System	2:1 Interlace	
Gamma Correction	0.45	
Horizontal Sync. Frequency	15.734KHz	
Vertical Sync. Frequency	60Hz	
Video Output	Composite: 1.0 Vp-p / 75 Ohm	
Power Source	12 VDC	
Power Consumption	120mA	300mA
Operation Temperature	-10° ~ 50°C (14° ~ 122°F) Less Than 80% RH	
Standard Lens	f3.6mm (Optional 2.8mm to 25mm Available)	
Dimensions (W x H)	5.12" x 2.29" (130 x 58mm)	
Weight	12.34 Oz. / 350 g. / 0.77 Lbs.	



LIMITED LIABILITY WARRANTY

Your new Camera is guaranteed to be free from defects in materials and workmanship for a period of three years from the date of purchase.

The product must have been used only for its intended purpose, and not been subjected to damage by misuse, willful or accidental damage, caused by excessive voltage or lightning.

The product must not have been tampered with in any way then the guarantee will be considered null and void.

This guarantee does not affect your statutory rights.

Contact an Authorized VITEK reseller for all servicing needs.



28492 CONSTELLATION ROAD VALENCIA, CA 91355
WWW.VITEKCCTV.COM