



## VTM-LCD351

3.5" Color TFT LCD  
Service Monitor



- 3.5" TFT LCD Display
- Continuous Use up to 8 Hours on 8 "AA" Alkaline Batteries
- Comes Complete with Vinyl Carrying case with Belt Clip and Strap
- BNC Input with BNC Patch Cable Included



BLACK



**CAUTION**  
**RISK OF ELECTRICAL SHOCK**  
**DO NOT OPEN**



1. Unit contains uninsulated dangerous voltage within the enclosure that may be of sufficient magnitude to constitute a risk of electric shock to persons
  2. Only use DC Power Supply
  3. Read & Keep these instructions.
  4. Heed to all warnings and follow all instructions carefully.
  5. Do not use near water.
  6. Clean only with dry cloth.
  7. Do not block any ventilation openings. install in accordance with the instructions.
  8. Do not install near any heat source such as radiators, heat resisters, stoves, or other apparatus (including amplifiers) that produce heat.
  9. Do not defeat the safety purpose of the polarized or grounding-type plug. A polarized plug has to blades with one wider the other. A grounding type plug has to blades and a third grounding plug. The wide blade or the third prong are provided for safety. if the provided plug dose not fit into your into your outlet, consult an electrician for replacement of the obsolete outlet.
  10. Protect the power cord from being walked on a pinched particularly at plugs, convenience receptacle, and the point where they exit from the apparatus.
  11. Only use attachment/accessories specified by VITEK.
  12. Use only with cart, stand, tripod, bracket, or table specified by the manufacturer, or sold with the Unit,
  13. Unplug this unit during lightning storms or when unused for long periods of time.
  14. Refer all servicing to qualified service personnel, Servicing is required when the unit has been damaged in any way, such as power-supply cord or plug is damaged, liquid has been spilled or objects have fallen into the unit, the unit has been exposed to rain or moisture, does not operate normally or has been dropped.
  15. Do not attempt to service this product yourself as opening or removing covers may expose you to dangerous voltage or other hazards. Refer all servicing to qualified service personal.
- CAUTION** - To reduce the risk of electric shock, do not perform any servicing other than contained in these operating instructions unless you are qualified to do so.

## SPECIFICATIONS

### VTM-LCD351

Display	3.5" Color TFT
Pixel Resolution	480 x 234
Input signal	1.0 Vp-p composite, 75 $\Omega$
Video Input	BNC Connection
Display system	NTSC.PAL
Power Input	8 AA Batteries (Not Included) or 12VDC Power Supply (Not Included)
Power Consumption	3.8W
Dimensions (W x H x D)	3.35" x 5.91" x 2.88" (85mm x 150mm x 73mm)
Weight	10.16 Oz.(188g)
Included Accessories	Vinyl Case, Carry Strap, BNC Patch Cable, 12VDC Patch Cable with Tee-Connector



## LIMITED LIABILITY WARRANTY

Your new Monitor is guaranteed to be free from defects in materials and workmanship for a period of two years from the date of purchase.

The product must have been used only for its intended purpose, and not been subjected to damage by misuse, willful or accidental damage, caused by excessive voltage or lightning.

The product must not have been tampered with in any way then the guarantee will be considered null and void.

This guarantee does not affect your statutory rights.

Contact VITEK directly for all servicing.



28492 CONSTELLATION ROAD VALENCIA, CA 91355  
WWW.VITEKCCTV.COM | 888-VITEK-70