



FEATURES

- 12VDC Multi-Output
- 4 to 18-Output Terminal strip connection
- UL Approved
- 5~30 Amp Output
- PTC (Resettable) Fuse
- Power indicator light on battery back-up units
- Lifetime Warranty

Detailed Specifications	VT-1205A-D4B	VT-1210A-D9B	VT-1230A-D18
Input Voltage	110 ~ 220VAC	110 ~ 220VAC	110 ~ 220VAC
Input Voltage Frequency	50/60Hz	50/60Hz	50/60Hz
Output Voltage	12VDC / 13.8V	12VDC +/-10%	12VDC +/-5%
Total Output Current	5A / 0.5	10A	30A
Total Outputs	4 Channels	9 Channels	18 Channels
Fuse Type	PTC (Resettable) Fuse	PTC (Resettable) Fuse	PTC (Resettable) Fuse
Fuse Rating	1.6A	1.6A	1.85A
Battery Backup	7AH Battery (Optional)	7AH Battery (Optional)	N/A
Dimensions	8.66" x 7.09" x 3.15" (220x180x80mm)	8.66" x 7.87" x 2.76" (220x200x70mm)	10.63" x 10.24" x 3.15" (270x260x80mm)
Weight	3.09 Lbs. (1.4KG)	3.31 Lbs. (1.5KG)	5.95 Lbs. (2.7KG)