


VT-710S

B/W Video Entry System



Wall Mount Plate



Power Supply



Recessed Mount

The VT-710S Video Door Entry System Features Extremely Low-Light Image Reproduction as well as Clear, Crisp Audio. The Attractive Monitor Station Combines Modern Styling and Hands-Free or Handset Communication for Privacy. The System Features a Door Release for Commercial Applications and the Versatile Door Camera may be Surface or Recess Mounted. The VT-710S Works Over Only 2 Wires and Can Replace a Standard Door Bell.

FEATURES

- 1/3" B/W CCD Outdoor Camera
- 4" B/W Flat CRT w/400 TV Lines
- Front Panel Door Release
- Automatic or Manual Monitor Activation
- Flush Mount Kit Included
- 2 Wire Telephone Call System



Industrial Video Products, Inc.

(888) VITEK-70 | WWW.VITEKCCTV.COM

9970 Glenoaks Blvd. Sun Valley, CA 91352 | Local: (818) 771-0300 Fax: (818) 771-0400

VT-710S

B/W Video Entry System

Detailed Specifications

INDOOR MONITOR:	
Monitor	4" B/W Flat CRT
Scanning Frequency	Horizontal 15.750 HZ (EIA) / 15.625HZ(CCIR)
Power	Free voltage (AC 100V-240V,50/60 HZ)
Power Consumption	13W(Activating), 2W(Stand by)
Resolution	400 TV LINES
Input Signal	Composite Video 75 ohm 1Vp-p
External Jack, Input Jack	Terminal Screw
Calling System	2 Strokes (Ding Dong)
Dimensions	7.09"(W) x 8.67"(H) x 2.05"(D)
OUTDOOR CAMERA:	
CCD	B/W 1/3" CCD
SYNC System	Internal
Frame	30/sec
Lens	F=2 Fixed Focus / 92° Angle of View
Illumination	0.5 LUX at 14.76" Distance
Power	DC 12V
Power Consumption	3W
Telephone call system	2 WIRES
Signal System	EIA / CCIR
Scanning System	525 Lines / 625 Lines
Operating Temperature	14° ~ 122° F
Auto Iris	Internal ALC System
Microphone	Condenser type
Audio Amplifier	RX & TX
Dimensions (mm)	3.55"(W) x 4.73"(H) x 1.85"(D)



Industrial Video Products, Inc.

(888) VITEK-70 | WWW.VITEKCCTV.COM

9970 Glenoaks Blvd. Sun Valley, CA 91352 | Local: (818) 771-0300 Fax: (818) 771-0400