

VITEK

PERFORMANCE YOU NEED
QUALITY YOU TRUST

VT-DVR01 / VT-DVR01A

SINGLE CHANNEL DIGITAL VIDEO RECORDERS



FEATURES:

- ▶ DIRECT VCR REPLACEMENT
- ▶ FOUR USER ASSIGNABLE RECORDING QUALITY MODES
- ▶ QUICK SEARCH BY TIME, EVENT OR ALARM
- ▶ 60 IPS MAXIMUM RECORDING
- ▶ COMPATIBLE WITH MOST NAME-BRAND MULTIPLEXERS
- ▶ PURCHASE YOUR OWN HARDDRIVE OR CHOOSE FROM 40, 80, 120 OR 180GB INSTALLED

The VT-DVR01 and VT-DVR01A single channel DVR's combine high quality digital video recordings with the operating ease of a VCR. They are capable of delivering images with resolution above that of super VHS with versatile recording modes from 1 to 60 images per second. Audio recording is also available with model VT-DVR01A.

PRELIMINARY SPEC SHEET


VITEK

Industrial Video Products, Inc.


"Quality Products At An Affordable Price"

Specifications	VT-DVR01	VT-DVR01A
Video Format	NTSC / EIA or PAL / CCIR	NTSC / EIA or PAL / CCIR
HDD Storage	IDE Type, UDMA 66 above, 1 removable HDD supported	IDE Type, UDMA 66 above, 1 removable HDD supported
Record Mode	Manual / Alarm / External / Timer	Manual / Alarm / External / Timer
Playback Search	Date & Time / Event / Alarm searching	Date & Time / Event / Alarm searching
RS232	Yes	Yes
O.S.D. (On Screen Display)	Yes	Yes
Security	Password protection	Password protection
Video Input	1 video input, composite 1 Vp-p / 75Ω (BNC)	1 video input, composite 1 Vp-p / 75Ω (BNC)
Video Output	1 video output, composite 1 Vp-p / 75Ω (BNC)	1 video output, composite 1 Vp-p / 75Ω (BNC)
Video Resolution	720 X 436 (NTSC) / 720 x 576 (PAL)	720 X 436 (NTSC) / 720 x 576 (PAL)
Video Compression	Wavelet	Wavelet
Display Refresh Rate	60 ips (NTSC) / 50 ips (PAL)	60 ips (NTSC) / 50 ips (PAL)
Record Refresh Rate	60 ips (NTSC) / 50 ips (PAL)	60 ips (NTSC) / 50 ips (PAL)
Alarm Input	TTL input: High (5V) / Low (GND)	TTL input: High (5V) / Low (GND)
Alarm Output	COM / NO	COM / NO
Video Loss Detection	Yes	Yes
Time Display Format	Yes	Yes
Audio Operation	No	Yes
Power Source	AC90 ~ 240V switching adaptor	AC90 ~ 240V switching adaptor
Power Consumption	<27W	<27W
Dimensions (W x H x D)	14.96" x 2.55" x 10.62" (380mm x 65mm x 270mm)	14.96" x 2.55" x 10.62" (380mm x 65mm x 270mm)
Weight	11.46lbs. / 5.2kgs	11.46lbs. / 5.2kgs
Operation Temperature	5° ~ 40° C (41° ~ 104° F)	5° ~ 40° C (41° ~ 104° F)

VT-DVR01



VT-DVR01A



9970 GLENOAKS BLVD. UNIT B SUN VALLEY, CA 91352
PHONE: 888-VITEK-70 818-771-0300 FAX: 818-771-0400
WWW.VITEKCCTV.COM