

VT-SMKC1 / VT-SMKC1/H

Side View Color Smoke
Detector Cameras



Discreet surveillance made easy. These simple plug and play cameras allow for vertical adjustment to obtain the optimum viewing angle with ease. Comes standard with a 3.6mm wide angle lens. Optional lenses are also available ranging from 2.9mm to 25mm.

FEATURES

- Color CCD Image Sensor with 420 TV Lines (VT-SMKC1) / 550 TV Lines (VT-SMKC1/H)
- Minimum Illumination of 0.5 Lux
- Camera Mounted On Adjustable Gimbal To Achieve the Perfect Viewing Angle
- 3.6mm Standard lens Included (Optional 2.8mm to 25mm Available)
- Dimensions: 5.12" (OD) X 2.29" (H)



(888) VITEK-70 | WWW.VITEKCCTV.COM
28492 Constellation Road Valencia, CA 91355

VT-SMKC1 / VT-SMKC1/H

Side View Color Smoke
Detector Cameras

Detailed Specifications	VT-SMKC1	VT-SMKC1/H
Image Device	1/4" DSP Color Panasonic CCD Image Sensor	1/3" DSP Color Panasonic CCD Image Sensor
Effective Pixels	510 x 492	768 x 492
Resolution	420 TV Lines	550 TV Lines
Minimum Illumination	0.5 Lux	
S/N Ratio	More Than 48dB	
Electronic Shutter	1/60 to 1/100,000 sec.	
AGC	On	
Sync. Mode	Internal Sync.	
Scanning System	2:1 Interlace	
Gamma Correction	0.45	
Horizontal Sync. Frequency	15.734KHz	
Vertical Sync. Frequency	60Hz	
Video Output	Composite: 1.0 Vp-p / 75 Ohm	
Power Source	12VDC	
Power Consumption	120mA	300mA
Operation Temperature	-10° ~ 50°C (14° ~ 122°F) Less Than 80% RH	
Standard Lens	f3.6mm (Optional 2.8mm to 25mm Available)	
Dimensions (W x H)	5.12" x 2.29" (130 x 58mm)	
Weight	12.34 Oz. / 350 g. / 0.77 Lbs.	

