

## VTD-B72 / C75 / C14

### B/W & COLOR INDOOR DOME CAMERAS



#### VTD-B72:

- ▶ 1/3" B/W SONY CCD WITH 400 TVL
- ▶ 0.1 LUX SENSITIVITY
- ▶ ATTRACTIVE AND COMPACT
- ▶ CHOOSE FROM BLACK OR WHITE BASE AND BUBBLE

#### VTD-C75:

- ▶ 1/3" COLOR SONY CCD WITH 420 TVL
- ▶ 0.5 LUX SENSITIVITY
- ▶ ATTRACTIVE AND COMPACT
- ▶ CHOOSE FROM BLACK OR WHITE BASE AND BUBBLE

#### VTD-C14:

- ▶ 1/4" COLOR PANASONIC CCD WITH 380 TVL
- ▶ 1.0 LUX SENSITIVITY
- ▶ ATTRACTIVE AND COMPACT
- ▶ CHOOSE FROM BLACK OR WHITE BASE AND BUBBLE

*Also Available  
In White!*

The B/W (VTD-B72) and Color (VTD-C75 & VTD-C14) Indoor Dome Cameras deliver sharp, natural images at a very low overall cost. These small yet attractive cameras are an excellent choice for convenience stores or office buildings. They accept 12 VDC power input for ease of use in remote or covert installations.

Specifications	VTD-B72	VTD-C75	VTD-C14
Image Device	1/3" B/W Sony CCD image Sensor	1/3" Color Sony CCD Image Sensor	1/4" Color Panasonic CCD image sensor
Effective Pixels	512 x 492	510 x 492	512 x 492
Resolution	400 TV Lines	420 TV Lines	380 TV Lines
Minimum Illumination	0.1 Lux / F2.0	0.5 Lux / F2.0	1 Lux / F2.0
S/N Ratio	More Than 48dB	More Than 48 db	More Than 48dB (AGC Off)
Electronic Shutter	1/60 to 1/100,000 sec.	1/60 to 1/100,000 sec.	1/60 to 1/100,000 sec.
Gamma Correction	N/A	N/A	0.45
White Balance	N/A	Auto White Balance	Auto White Balance
AGC	N/A	N/A	Yes
BLC Function	N/A	Auto Detect	N/A
Lens Angle	92°	92°	70°
Video Output	Composite: 1.0 Vp-p / 75Ω	Composite: 1.0 Vp-p / 75Ω	Composite: 1.0 Vp-p / 75Ω
Power Source	12VDC (+/-10%)	12VDC (+/-10%)	12VDC (+/-10%)
Power Consumption	120mA	120mA	80mA
Standard Lens	f3.6mm / F2.0 (2.9/6/8/12mm Optional)	f3.6mm / F2.0 (2.9/6/8/12mm Optional)	f3.6mm / F2.0 (2.9/6/8/12mm Optional)
Dimensions (W x H)	3.43" x 3.18"	3.43" x 3.18"	3.43" x 3.18"
Weight	280 g. / 9.87 oz. / 0.611 lbs.	280 g. / 9.87 oz. / 0.611 lbs.	280 g. / 9.87 oz. / 0.611 lbs.