

# Indoor WDR Mighty Dome Cameras

700 TV Line WDR  
Dome Camera Series



Lighting conditions play a critical role in producing useable video images in a surveillance system. The Pixim-Powered WDR Dome Camera was created to meet and solve the challenges brought on by varying lighting conditions within a single capture area.

By use of the PIXIM Seawolf Wide Dynamic Range DSP we are able to control and display clear crisp images in varied lighting conditions more accurately than ever before. Its improved resolution of 700TV Lines is unequaled by any other WDR Surveillance camera. Advanced on screen display and True ICR Day/Night function are among the many other features which place this camera at the best in its class.

## FEATURES

- Pixim D8800C Seawolf Digital Imaging System CMOS
- 700 TVL High Resolution
- WDR - Wide Dynamic range
- 3DNR - Three Dimensional Motion Adaptive Noise Reduction
- Secondary Video Output (Cable Included)
- OSD (On Screen Display) for Camera Function Setup
- Flush or Surface mount
- Infinity Ball Mount for Any Viewing Angle
- UTP Interface Option Available
- UTC CONTROL - Serial Control over Coax
- 1" Conduit Knockout
- Available in Ivory or Black color
- With Night Watch DSS Low Light Color Technology
- Dual Voltage 12VDC & 24VAC

## Example of WDR



Conventional Camera

VTD-MVP2910WDR



Available Configurations Include:

### VTD-MP2810WDR

Indoor Pixim Seawolf Powered WDR Mighty Dome 700TVL Camera w/2.8-10mm Lens, OSD, Day Night w/ICR and "Night Watch" DSS -12VDC/24VAC

### VTD-MP922WDR

Indoor Pixim Seawolf Powered WDR Mighty Dome 700TVL Camera w/9-22mm Lens, OSD, Day Night w/ICR and "Night Watch" DSS -12VDC/24VAC



(888) VITEK-70 | [WWW.VITEKCCTV.COM](http://WWW.VITEKCCTV.COM)  
28492 Constellation Road Valencia, CA 91355

# Indoor WDR Mighty Dome Cameras

700 TV Line WDR  
Dome Camera Series

Detailed Specifications	NTSC	PAL
Image Device	Pixim D8800C Seawolf Digital Imaging System CMOS	
Effective Pixels	758(H) x 540(V)	
Scan Frequency	59.94HZ(V), 15.734K HZ(H)	50HZ(V), 15.625KHZ(H)
Synchronization	Internal / Line Lock (phase adjust)	
H. Resolution	700TVL	
Sensitivity	0.00008Lux at F1.2@40IRE, 32x (DSS+ICR mode)	
S/N Ratio	More than 52dB with AGC OFF at 50IRE	
White Balance	2,000 ~ 11,000°K Automatic tracking / AWB / MANUAL	
WDR Mode	[Low / Middle / High / Custom (User adjustment)]	
Motion Detection	On / Off (4 Programmable Zone)	
Digital Zoom	Up to X12 Digital Zoom	
FLIP	OFF / H-FLIP / V-FLIP / H/V-FLIP	
Privacy Zone	On / Off (6 Programmable Zone)	
Auto Iris Control	DC Drive Iris Control	
SLOW SHUTTER	2 ~ 32X	
Day & Night	Infrared Cut-Filter Removable built-in	
Lens Options	F1.2 2.8~10mm DC Auto Iris IR Corrected ICR / F1.8 9~22mm DC Auto Iris IR Corrected ICR	
Video Output	VBS 1 Vpp +/- 10%, 75ohm	
Operating Power	12VDC / 24VAC 3 Watts / 220 mAmp	
Operating Condition	-4°F ~ 122°F / -20°C ~ 50°C, 85% RH. Max. Non-condensing	
Dimensions (H x Dia.)	4.45" x 5.71" (113mm x 145mm)	
Weight (Camera)	1lb / .46Kg	
Weight (Carton)	1.6lb / .72Kg	



**VT-MDPLMT**  
Mighty Dome Pole Mount



**VT-MDCNMT**  
Mighty Dome Corner Mount







**VT-MD/CMT**  
Mighty Dome Ceiling Mount



**VT-MD/WMT**  
Mighty Dome Wall Mount



**VTD-MD-FMP**  
Mighty Dome Flush Mount Decorator Plate



(888) VITEK-70 | [WWW.VITEKCCTV.COM](http://WWW.VITEKCCTV.COM)  
28492 Constellation Road Valencia, CA 91355