


VTD-VPH SERIES

Vandal Resistant Color Dome Cameras



Inside Dome



3-Axis Camera Mounting System



Removable Dome Ring For Recessed Mounting Applications

The VTD-VPH Vandal Resistant Dome Camera is a smaller, more attractive camera ideal for use in commercial or residential applications. It measures only 5" in diameter and comes with a 24 Volt AC power input for easy integration with standard cameras and power systems. Versatile mounting and lens options allow you to achieve perfect video images in virtually any environment. All VTD-VPH domes feature Sony Super-HAD and/or Ex-View Technology with Hi-Resolution of 480 Television Lines.

FEATURES

- 480 TV Lines Resolution
- Patented 3-Axis Mount
- Compact 5" Diameter Dome May Be Surface or Semi Flush Mounted (Adapter Included)
- Weather Resistant
- Several Design Options to Meet Every Application Including Fixed, Auto Iris Varifocal, and Day Night.
- Dual Voltage: 12VDC / 24VAC



Industrial Video Products, Inc.

(888) VITEK-70 | WWW.VITEKCCTV.COM

9970 Glenoaks Blvd. Sun Valley, CA 91352 | Local: (818) 771-0300 Fax: (818) 771-0400

VTD-VPH SERIES

Vandal Resistant Color Dome Cameras

Detailed Specifications	VTD-VPH/FIXED	VTD-VPH266	VTD-VPH412	VTD-VPH922
Image Device	1/3" High Resolution Super HAD Color CCD			
Effective Pixels	768 x 494			
Resolution	480 TV Lines			
Minimum Illumination	0.7 Lux / F1.2 (AGC On)			
S/N Ratio	More than 48dB (AGC off)			
Electronic Shutter	1/60 to 1/100,000 Sec.			
AGC	Built-In (On)			
Lens	3.6mm Fixed Iris *	2.6-6.0mm Varifocal	3.7-12mm Varifocal	9.0-22mm Varifocal
Video Output	Composite: 1.0 Vp-p / 75 Ohm			
White Balance	Auto White Balance (AWB)			
Power Source	Dual Voltage: 12VDC / 24VAC			
Weight	750 g. / 26.46 Oz. / 1.65 Lbs.			
Dimensions	160mm x 99mm / 6.29" x 3.89" (D x H)			
Construction	Aluminum/Tin Base - Polycarbonate Bubble			
IP Rating	IP66/68			
Operation Temperature	14° ~ 122° Fahrenheit			

Detailed Specifications	VTD-VPH266DN	VTD-VPH412DN	VTD-VPH922DN
Image Device	1/3" High Resolution Super HAD Color CCD		
Effective Pixels	768 x 494		
Resolution	480 TV Lines		
Minimum Illumination	0.03 Lux / F1.2 (AGC On) With Day/Night Function		
S/N Ratio	More than 48dB (AGC off)		
Electronic Shutter	1/60 to 1/100,000 Sec.		
AGC	Built-In (On)		
Lens	2.6-6.0mm Varifocal	3.7-12mm Varifocal	9.0-22mm Varifocal
Video Output	Composite: 1.0 Vp-p / 75 Ohm		
White Balance	Auto White Balance (AWB)		
Power Source	Dual Voltage: 12VDC / 24VAC		
Weight	750 g. / 26.46 Oz. / 1.65 Lbs.		
Dimensions	160mm x 99mm / 6.29" x 3.89" (D x H)		
Construction	Aluminum/Tin Base - Polycarbonate Bubble		
IP Rating	IP66/68		
Operation Temperature	14° ~ 122° Fahrenheit		

* 3.6mm Lens Is Standard (2.9, 6.0, 8.0, 12mm Available By Special Order)



Industrial Video Products, Inc.

(888) VITEK-70 | WWW.VITEKCCTV.COM

9970 Glenoaks Blvd. Sun Valley, CA 91352 | Local: (818) 771-0300 Fax: (818) 771-0400