

VTM-LED220P / 240P

22" & 24" Professional LED Monitors with HDMI, VGA, and Dual Looping BNC's



FEATURES

- 22" / 24" Wide Screen LED Display Panel
- HDMI, VGA, and Dual Looping BNC Composite Video Inputs & Stereo Audio Input
- Resolution up to 1920 x 1080 (1080P)
- Contrast Ratio of 10,000:1
- <5ms Response time
- 170° Horizontal Viewing Angle
- Picture In Picture (PIP) / POP (Picture On Picture) Display Options
- Top Panel Controls with included IR Remote Control
- VESA 100mm Standard Mounting
- 50,000 Hour Panel Life



VTM-LED220P / VTM-LED240P Rear Connections



(888) VITEK-70 | WWW.VITEKCCTV.COM
28492 Constellation Road Valencia, CA 91355

VTM-LED220P / 240P

22" & 24" Professional LED Monitors with HDMI, VGA, and Dual Looping BNC's

Detailed Specifications	VTM-LED220P	VTM-LED240P
Screen Size	21.5"	23.6"
Display Type	LED	
Aspect Ratio	16:9	
Resolution	1080P (1920x1080)	
Response Time	<5ms	
Contrast Ratio	10,000:1	
Display Color	16.7 Million	
Brightness	300cd/m ²	
Pixel Type	Active Matrix TFT	
Pixel Pitch	0.24825 x 0.24825 mm	0.2715 x 0.2715 mm
Viewing Angle (H/V)	170° / 160°	
Video System	NTSC/PAL	
Video In/Out	2 BNC Inputs / 2 BNC Outputs (Looping)	
VGA In	1 (15Pin D-Sub)	
HDMI In	1	
Audio Input	Stereo RCA & 1/8" PC	
Built In speaker	Yes (1.5W x 2)	
PIP / POP	Analog / Digital	
Remote	Optional	
3D Comb Filter	YES	
3D De-Interlace	YES	
Noise Reduction	YES	
Multi-Language	English, Spanish, German, French, Italian, Russia, Turkish, Japanese, Polish	
Stand Tilt	0°~15°	
Vesa Mount Size	100mm x 100mm	
Power Adapter	12VDC (AC100/240 [50/60])	
Power Consumption	30W Max	35W Max
Certifications	UL, FCC-DOC, CE, ROHS	
Operating Temperature	32° to 104° F (0° to 40° C)	
Operating Humidity	10% to 90% relative, non-condensing	
Dimensions (w/Stand)	20.63" x 14.76" x 6.7" (524 x 375 x 170mm)	22.83" x 16.02" x 6.7" (580 x 407 x 170mm)
Weight	7.93 lbs (3.6Kgs)	9.7 lbs (4.4Kgs)

