



The VTM-15F Offers high resolution and high contrast pictures with solid state circuitry for a long service life. The cabinet is built with a rugged, attractively styled steel. A regulated power supply maintains excellent performance during fluctuations in line voltage. Digital controls for Tint, Color, Brightness, Contrast, Volume, and Power On/Off are located at the front of the unit.

FEATURES

- Resolution of more than 520 lines at center on a 15" diagonal screen
- Sequential with adjustable dwell A,B & Y/C
- Attractive black metal cabinet with recessed handles for portability
- Digital front panel controls
- Looping Video Inputs
- Audio in / audio out
- Y/C in-out

Detailed Specifications	
Picture Tube	15" Diagonal
System	NTSC / PAL Auto Detect
Front Panel Controls	Power ON/OFF / VIDEO (A / B / Y/C) / MENU / ENTER / UP / DOWN / UNDERSCAN
Display Resolution	520 TV lines
Input Signal	1Vp-p Composite Video
Input Impedance	75 ohm (Auto Termination)
Bandwidth	8MHz
Video Gain	30dB
Linearity	Horizontal: 10%(Max), Vertical 10% (Max)
Operating System	NTSC:525 lines / Frame; PAL:625 lines / Frame
Video (In / Out)	BNC: Input x 2 / Output x 2 / S-Video Input x 1 / Output x1
Audio (In / Out)	RCA Jack: Input x 2 / Output x 2
Audio Input Signal	1 Vp-p
Audio Amplifier	1W / 8 ohm
Input Voltage	AC 96~256V, 50Hz/ 60Hz
Power Consumption	63 W
Operation Temperature	50~130°F (-10~55°)
Dimensions (W x D x H)	14.25" x 13.46" x 12.6" (362 x 342 x 320mm)
Weight (Net/Gross)	30.86 lbs. (14kg.)

VTM-15CF Rear Connections:

